QJ/QJR 型 井用 / 地热潜水电泵

QJ/QJR type well/terrestrial heat submersible electric pump



产品简介 Product introduction

QJ型井用潜水电泵是潜水电机与潜水泵直联一体，潜入水中工作的提水机具。主要适用于农田灌溉，城市、工矿企业的给排水工程。

QJR 型潜水电泵适用于水温为 100℃ 以下的地下热水的开采，具有耐热、防腐、抗老化等特点。

QJ type well submersible electric pump is a kind of water-lifting machine with submersible motor and submersible pump integrated directly into one set, working deep into the water. It is mainly used in the feeding and draining engineering of farmland irrigation, city, industrial and mine establishments.

QJR type geothermal submersible electric pump can be used in the exploitation of underground hot water with a temperature under 100℃, featuring heat-resisting, corrosion resistance, anti-aging, etc.

流　量：2 – 1000m³/h
Discharge capacity: 2 – 1000m³/h

扬　程：10m – 1000m
Lift head: 10m – 1000m

电机功率：0.55kW – 600kW
Motor power: 0.55kW – 600kW

额定电压：380V/660V
Rated voltage: 380V/660V

主要用途 Main uses



深井提水
Lift water from deep well



水池江河排水
Drain water from pool, river



高层建筑供水
Water supply for skyscraper

型号说明 Type explanation

200　QJ　50 - 52 / 4

- 叶轮级数 Stage number of impeller
- 扬程 Lift head(m)
- 流量 Capacity(m³/h)
- 井用潜水泵 Well submersible pump
- 使用最小井径 Minimum well diameter(mm)

200 QJR 50 - 52 / 4

- 叶轮级数 Stage number of impeller
- 扬程 Lift head(m)
- 流量 Capacity(m^3/h)
- 井用地热潜水泵 Well terrestrial heat submersible pump
- 使用最小井径 Minimum well diameter(mm)

结构说明 Structure explanation

1. 潜水电泵装置由水泵、电机、输水管道、防水电缆和控制开关五大部分组成，水泵为单吸多级立式离心泵。
2. 潜水电机采用 YQS 型充水湿式结构，内腔充满清水，主要用于电机冷却及轴承润滑。在运转过程中由于温度变化，引起电机内腔充水体积变化时，可由电机下端调压装置自动调节。
3. 为防止泥砂浸入电机，在电机上端装有由甩砂器和骨架油封组成的防砂机构。
4. 电机上端设有注水孔及排气孔，下端设有放水孔。
5. 电机下部装有止推轴承及推力盘，主要承受电泵的轴向力。
6. 电机的定子绕组采用耐水电磁线，有良好的绝缘和耐水性能，转子为鼠笼型结构。
7. 用于腐蚀性水质时，采用不锈钢潜水电泵。

1. Submersible electric pump is composed of five parts: water pump, motor, water line, waterproof cable and control switch. Water pump belongs to single suction multistage vertical centrifugal pump.
2. Submersible motor adopts YQS type water-filled wet structure, the chamber full of clear water, mainly for cooling the motor and the bearing lubrication. During operation, as the temperature changing may cause the water-filling volume to vary, a pressure regulator is equipped in the motor to allow the calibration.
3. For preventing the sand getting into the motor, a sand-preventing sealing mechanism consisting of a sand thrower and a mechanical sealis mounted on the upside motor, composing a sand-preventing structure, the whole motor is well sealed by its sealing structure.
4. There are water injection hole and exhaust hole in the upper part of the motor and discharge hole in the lower part.
5. Thrust bearing and thrust collar are installed at the lower part of motor, mainly subjected to the axial force of the electric pump.
6. The winding of motor stator adopts water-proof electromagnetic wire with good insulating and water-proof functions and rotor adopts squirrel-cage structure.
7. The stainless steel submersible pump is used for corrosive water quality.

YQS/YQSR 潜水电机结构图

YQS/YQSR Submersible Motor Structure



QJ/QJR 潜水泵结构图

QJ/QJR Submersible Pump Structure



基本参数表 Basic parameter table

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
1	150QJ5-50/7	628	24	3	762	52.5	2850	1.5	3 × 2.5	143
2	150QJ5-78/11	796	34	3	762	52.5			3 × 2.5	
3	150QJ5-100/14	965	40	3	762	52.5			3 × 4	
4	150QJ5-128/18	1133	48	4	772	53.5			3 × 4	
5	150QJ5-150/21	1310	54	4	772	53.5			3 × 4	
6	150QJ5-178/25	1478	62	5.5	802	56.5			3 × 6	
7	150QJ5-200/28	1698	68	5.5	802	56.5			3 × 6	
8	150QJ5-250/35	2088	82	7.5	862	62.5			3 × 6	
9	150QJ5-300/42	2427	96	9.2	902	67			3 × 10	
10	150QJ10-50/7	663	23	3	762	52.5		2	3 × 2.5	
11	150QJ10-78/11	851	34	4	772	53.5			3 × 4	
12	150QJ10-100/14	1035	42	5.5	802	56.5			3 × 4	
13	150QJ10-128/18	1227	35	7.5	862	62.5			3 × 6	
14	150QJ10-150/21	1416	43	7.5	862	62.5			3 × 6	
15	150QJ10-178/25	1650	54	9.2	902	67			3 × 6	
16	150QJ10-200/28	1838	62	11	982	74			3 × 10	
17	150QJ10-250/35	2261	81	13	1022	77			3 × 10	
18	150QJ10-300/42	2637	100	15	1092	84			3 × 16	
19	150QJ20-26/4	470	25	3	762	52.5			3 × 2.5	
20	150QJ20-33/5	570	27	3	762	52.5			3 × 2.5	
21	150QJ20-39/6	670	32	4	772	53.5			3 × 4	
22	150QJ20-46/7	770	37	5.5	802	56.5			3 × 4	
23	150QJ20-52/8	870	42	5.5	802	56.5			3 × 4	
24	150QJ20-59/9	970	54	5.5	802	56.5			3 × 4	
25	150QJ20-65/10	1070	59	7.5	862	62.5			3 × 4	
26	150QJ20-72/11	1295	64	7.5	862	62.5			3 × 4	
27	150QJ20-78/12	1395	70	7.5	862	62.5			3 × 6	
28	150QJ20-85/13	1495	75	9.2	902	67			3 × 6	
29	150QJ20-91/14	1595	80	9.2	902	67			3 × 6	
30	150QJ20-98/15	1695	85	9.2	902	67			3 × 6	
31	150QJ20-104/16	1795	90	11	982	74			3 × 6	
32	150QJ20-111/17	1895	95	11	982	74			3 × 6	
33	150QJ20-117/18	1995	100	13	1022	77			3 × 6	
34	150QJ20-124/19	2095	105	13	1022	77			3 × 6	
35	150QJ20-130/20	2195	110	13	1022	77			3 × 6	
36	150QJ20-137/21	2295	115	15	1092	84			3 × 6	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
37	150QJ20-143/22	2395	120	15	1092	84	2850	2	3 × 10	143
38	150QJ20-150/23	2495	125	15	1092	84			3 × 10	
39	150QJ20-156/24	2595	131	15	1092	84			3 × 10	
40	150QJ20-163/25	2795	136	15	1092	84			3 × 10	
41	150QJ20-170/26	2895	141	18.5	1132	87			3 × 10	
42	150QJ20-176/27	2995	146	18.5	1132	87			3 × 10	
43	150QJ20-182/28	3095	151	18.5	1132	87			3 × 10	
44	150QJ25-24/3	425	19	3	762	52.5		2.5	3 × 2.5	
45	150QJ25-32/4	540	25	4	772	53.5			3 × 4	
46	150QJ25-40/5	655	31	5.5	802	56.5			3 × 4	
47	150QJ25-48/6	770	38	5.5	802	56.5			3 × 4	
48	150QJ25-56/7	885	44	7.5	862	62.5			3 × 4	
49	150QJ25-64/8	1000	50	7.5	862	62.5			3 × 4	
50	150QJ25-72/9	1240	57	9.2	902	67			3 × 6	
51	150QJ25-80/10	1355	66	9.2	902	67			3 × 6	
52	150QJ25-88/11	1470	72	11	982	74			3 × 6	
53	150QJ25-96/12	1585	79	11	982	74			3 × 6	
54	150QJ25-104/13	1700	85	13	1022	77			3 × 6	
55	150QJ25-112/14	1815	91	13	1022	77			3 × 6	
56	150QJ25-120/15	1930	97	15	1092	84			3 × 6	
57	150QJ25-128/16	2045	103	15	1092	84			3 × 6	
58	150QJ25-136/17	2160	110	18.5	1132	87			3 × 10	
59	150QJ25-144/18	2275	116	18.5	1132	87			3 × 10	
60	150QJ25-152/19	2390	122	18.5	1132	87			3 × 10	
61	150QJ32-12/2	310	14	3	762	52.5			3 × 2.5	
62	150QJ32-18/3	425	20	3	762	52.5			3 × 4	
63	150QJ32-24/4	540	26	4	772	53.5			3 × 4	
64	150QJ32-30/5	655	32	5.5	802	56.5			3 × 4	
65	150QJ32-36/6	770	38	5.5	802	56.5			3 × 4	
66	150QJ32-42/7	885	46	7.5	862	62.5			3 × 6	
67	150QJ32-48/8	1000	50	9.2	902	67			3 × 6	
68	150QJ32-54/9	1115	57	9.2	902	67			3 × 6	
69	150QJ32-60/10	1230	73	11	982	74			3 × 6	
70	150QJ32-66/11	1345	78	11	982	74			3 × 6	
71	150QJ32-72/12	1585	83	13	1022	77			3 × 6	
72	150QJ32-78/13	1700	88	13	1022	77			3 × 6	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
73	150QJ32-84/14	1815	93	13	1022	77	2850	2.5	3 × 6	143
74	150QJ32-90/15	1930	98	15	1092	84			3 × 6	
75	150QJ32-96/16	2045	103	15	1092	84			3 × 6	
76	150QJ32-102/17	2160	109	18.5	1132	87			3 × 6	
77	150QJ32-108/18	2275	114	18.5	1132	87			3 × 10	
78	150QJ32-114/19	2390	120	18.5	1132	87			3 × 10	
79	150QJ40-8/1	210	9	3	762	52.5			3 × 2.5	
80	150QJ40-16/2	340	16	4	772	53.5			3 × 2.5	
81	150QJ40-24/3	470	23	5.5	802	56.5			3 × 4	
82	150QJ40-32/4	600	30	7.5	862	62.5			3 × 4	
83	150QJ40-40/5	730	37	9.2	902	67			3 × 4	
84	150QJ40-48/6	860	44	9.2	902	67			3 × 6	
85	150QJ40-56/7	990	51	11	982	74			3 × 6	
86	150QJ40-64/8	1120	58	13	1022	77			3 × 6	
87	150QJ40-72/9	1385	70	15	1092	84			3 × 6	
88	150QJ40-80/10	1515	77	18.5	1132	87			3 × 6	
89	150QJ40-88/11	1645	84	18.5	1132	87			3 × 6	
90	150QJ40-96/12	1775	91	18.5	1132	87			3 × 6	
91	150QJ50-6/1	210	24	3	762	52.5		3	3 × 2.5	
92	150QJ50-12/2	340	29	4	772	53.5			3 × 4	
93	150QJ50-18/3	470	34	5.5	802	56.5			3 × 4	
94	150QJ50-24/4	600	39	7.5	862	62.5			3 × 4	
95	150QJ50-30/5	730	44	9.2	902	67			3 × 4	
96	150QJ50-36/6	860	49	9.2	920	67			3 × 6	
97	150QJ50-42/7	990	54	11	982	74			3 × 6	
98	150QJ50-48/8	1120	59	13	1022	77			3 × 6	
99	150QJ50-54/9	1250	64	15	1092	84			3 × 6	
100	150QJ50-60/10	1380	69	18.5	1132	87			3 × 6	
101	150QJ50-66/11	1510	74	18.5	1132	87			3 × 6	
102	150QJ50-72/12	1775	97	18.5	1132	87			3 × 6	
103	175QJ10-15/1	220	13	3	710	52		2	3 × 2.5	168
104	175QJ10-30/2	340	21	3	710	52			3 × 2.5	
105	175QJ10-45/3	460	29	3	710	52			3 × 2.5	
106	175QJ10-60/4	580	37	4	715	53			3 × 2.5	
107	175QJ10-75/5	835	55	5.5	735	56			3 × 2.5	
108	175QJ10-90/6	955	63	5.5	735	56			3 × 2.5	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
109	175QJ10-105/7	1075	71	7.5	755	59			3 × 4	
110	175QJ10-120/8	1195	79	7.5	755	59			3 × 4	
111	175QJ10-135/9	1315	87	9.2	815	70			3 × 4	
112	175QJ10-150/10	1435	95	9.2	815	70			3 × 4	
113	175QJ10-165/11	1555	104	11	835	73			3 × 6	
114	175QJ10-180/12	1675	112	13	865	76			3 × 10	
115	175QJ10-195/13	1795	120	13	865	76			3 × 10	
116	175QJ10-210/14	1915	128	15	905	81			3 × 10	
117	175QJ10-225/15	2035	136	15	905	81			3 × 10	
118	175QJ10-240/16	2155	144	18.5	960	93			3 × 16	
119	175QJ10-255/17	2275	152	18.5	960	93			3 × 16	
120	175QJ10-270/18	2395	160	18.5	960	93			3 × 16	
121	175QJ10-285/19	2515	168	22	965	93.5			3 × 25	
122	175QJ10-300/20	2635	177	22	965	93.5			3 × 25	
123	175QJ15-14	220	16	3	710	52			3 × 2.5	
124	175QJ15-28/2	340	23	3	710	52			3 × 2.5	
125	175QJ15-42/3	460	31	4	715	53		2	3 × 2.5	168
126	175QJ15-56/4	580	39	5.5	735	56	2850		3 × 2.5	
127	175QJ15-70/5	835	58	7.5	755	59			3 × 4	
128	175QJ15-84/6	955	66	7.5	755	59			3 × 4	
129	175QJ15-98/7	1075	73	9.2	815	70			3 × 4	
130	175QJ15-112/8	1195	80	11	835	73			3 × 4	
131	175QJ15-126/9	1315	88	11	835	73			3 × 6	
132	175QJ15-140/10	1435	95	13	865	76			3 × 6	
133	175QJ15-154/11	1555	103	15	905	81			3 × 10	
134	175QJ15-168/12	1675	111	15	905	81			3 × 10	
135	175QJ15-182/13	1795	118	18.5	960	93			3 × 10	
136	175QJ15-196/14	1915	126	18.5	960	93			3 × 16	
137	175QJ15-210/15	2035	133	18.5	960	93			3 × 16	
138	175QJ15-224/16	2155	141	22	965	93.5			3 × 16	
139	175QJ15-238/17	2275	148	22	965	93.5			3 × 16	
140	175QJ15-252/18	2395	156	22	965	93.5			3 × 25	
141	175QJ15-266/19	2515	164	25	985	95			3 × 25	
142	175QJ20-26/2	340	25	3	710	52			3 × 2.5	
143	175QJ20-39/3	460	32	4	715	53			3 × 4	
144	175QJ20-52/4	580	39	5.5	735	56			3 × 4	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
145	175QJ20-65/5	700	46	7.5	755	59	2850	2	3 × 4	168
146	175QJ20-78/6	955	59	7.5	755	59			3 × 6	
147	175QJ20-91/7	1075	77	9.2	815	70			3 × 6	
148	175QJ20-104/8	1195	95	11	835	73			3 × 6	
149	175QJ20-117/9	1315	112	13	865	76			3 × 6	
150	175QJ20-130/10	1435	130	13	865	76			3 × 6	
151	175QJ20-143/11	1555	148	15	905	81			3 × 10	
152	175QJ20-156/12	1675	166	15	905	81			3 × 10	
153	175QJ20-169/13	1795	184	18.5	960	93			3 × 10	
154	175QJ20-182/14	1915	201	18.5	960	93			3 × 10	
155	175QJ20-195/15	2035	219	22	965	93.5			3 × 16	
156	175QJ20-208/16	2155	236	22	965	93.5			3 × 16	
157	175QJ20-221/17	2275	254	22	965	93.5			3 × 16	
158	175QJ20-234/18	2395	270	25	985	95			3 × 25	
159	175QJ20-247/19	2515	286	25	985	95			3 × 25	
160	175QJ32-24/2	340	23	4	715	53		2.5	3 × 4	
161	175QJ32-36/3	460	27	5.5	735	56			3 × 4	
162	175QJ32-48/4	580	31	7.5	755	59			3 × 4	
163	175QJ32-60/5	700	35	9.2	815	70			3 × 6	
164	175QJ32-72/6	955	39	11	835	73			3 × 6	
165	175QJ32-84/7	1075	43	13	865	76			3 × 6	
166	175QJ32-96/8	1195	79	15	905	81			3 × 6	
167	175QJ32-108/9	1315	83	18.5	960	93			3 × 6	
168	175QJ32-120/10	1435	87	18.5	960	93			3 × 10	
169	175QJ32-132/11	1555	91	22	965	93.5			3 × 10	
170	175QJ32-144/12	1675	95	22	965	93.5			3 × 10	
171	175QJ32-156/13	1795	99	25	985	95			3 × 16	
172	175QJ32-168/14	1915	103	25	985	95			3 × 16	
173	175QJ40-24/2	340	17	5.5	735	56			3 × 4	
174	175QJ40-36/3	460	26	7.5	755	59			3 × 4	
175	175QJ40-48/4	580	35	9.2	815	70			3 × 6	
176	175QJ40-60/5	700	44	11	835	73			3 × 6	
177	175QJ40-72/6	955	59	13	865	76			3 × 6	
178	175QJ40-84/7	1075	72	15	905	81			3 × 6	
179	175QJ40-96/8	1195	81	18.5	960	93			3 × 6	
180	175QJ40-108/9	1315	90	22	965	93.5			3 × 10	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
181	175QJ40-120/10	1435	101	22	985	95	2850	2.5	3 × 10	168
182	175QJ40-132/11	1555	110	25	985	95			3 × 10	
183	175QJ50-24/2	340	19	5.5	735	56		3	3 × 4	
184	175QJ50-36/3	460	27	9.2	815	70			3 × 4	
185	175QJ50-48/4	580	36	11	835	73			3 × 6	
186	175QJ50-60/5	700	45	13	865	76			3 × 6	
187	175QJ50-72/6	955	61	15	905	81			3 × 6	
188	175QJ50-84/7	1075	70	18.5	960	93			3 × 6	
189	175QJ50-96/8	1195	79	22	965	93.5			3 × 10	
190	175QJ50-108/9	1315	89	25	985	95			3 × 10	
191	200QJ10-47/3	400	29	4	670	67		2	3 × 2.5	184
192	200QJ10-62/4	505	39	5.5	690	70			3 × 2.5	
193	200QJ10-78/5	728	54	7.5	705	72			3 × 4	
194	200QJ10-93/6	833	64	7.5	705	72			3 × 4	
195	200QJ10-109/7	938	74	9.2	750	79			3 × 6	
196	200QJ10-124/8	1043	84	9.2	750	79			3 × 6	
197	200QJ10-140/9	1148	94	11	765	85			3 × 6	
198	200QJ10-155/10	1253	104	13	780	87			3 × 6	
199	200QJ10-171/11	1358	114	13	780	87			3 × 10	
200	200QJ10-186/12	1463	124	15	815	90			3 × 10	
201	200QJ10-202/13	1568	134	15	815	90			3 × 10	
202	200QJ10-217/14	1673	144	18.5	870	107			3 × 16	
203	200QJ10-233/15	1778	154	18.5	870	107			3 × 16	
204	200QJ10-248/16	1883	164	18.5	870	107			3 × 16	
205	200QJ10-264/17	1988	174	22	1030	124.5			3 × 25	
206	200QJ10-279/18	2093	184	22	1030	124.5			3 × 25	
207	200QJ10-295/19	2198	194	22	1030	124.5			3 × 25	
208	200QJ10-310/20	2303	204	25	1100	131.5			3 × 25	
209	200QJ10-326/21	2408	214	25	1100	131.5			3 × 25	
210	200QJ10-341/22	2513	224	25	1100	131.5			3 × 25	
211	200QJ10-355/23	2618	234	30	1165	145.5			3 × 35	
212	200QJ10-372/24	2828	244	30	1165	145.5			3 × 35	
213	200QJ10-388/25	2933	254	30	1165	145.5			3 × 35	
214	200QJ10-403/26	3038	264	30	1165	145.5			3 × 50	
215*	200QJ10-419/27	3143	274	37	1620	183			3 × 50	
216*	200QJ10-434/28	3248	284	37	1620	183			3 × 50	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
217*	200QJ10-450/29	3353	294	37	1620	183	2850	2	3 × 50	184
218*	200QJ10-465/30	3458	304	37	1620	183			3 × 50	
219*	200QJ10-481/31	3563	314	37	1620	183			3 × 70	
220*	200QJ10-496/32	3668	324	37	1620	183			3 × 70	
221*	200QJ10-512/33	3773	334	37	1620	183			3 × 70	
222*	200QJ10-527/34	3878	344	45	1725	202			3 × 70	
223*	200QJ10-543/35	3983	354	45	1725	202			3 × 70	
224*	200QJ10-558/36	4088	364	45	1725	202			3 × 95	
225*	200QJ10-574/37	4193	374	45	1725	202			3 × 95	
226*	200QJ10-589/38	4945	384	45	1725	202			3 × 95	
227*	200QJ10-605/39	5065	394	45	1725	202			3 × 95	
228*	200QJ10-620/40	5185	404	45	1725	202			3 × 95	
229*	200QJ10-636/41	5305	414	55	1885	217			3 × 120	
230*	200QJ10-651/42	5545	424	55	1885	217			3 × 120	
231*	200QJ10-667/43	5665	434	55	1885	217			3 × 120	
232*	200QJ10-682/44	5785	444	55	1885	217			3 × 120	
233*	200QJ10-698/45	5905	454	55	1885	217			3 × 120	
234*	200QJ10-713/46	6025	464	55	1885	217			3 × 120	
235*	200QJ10-729/47	6145	474	55	1885	217			3 × 120	
236*	200QJ10-744/48	6265	484	55	1885	217			3 × 150	
237*	200QJ10-760/49	6385	494	55	1885	217			3 × 150	
238*	200QJ10-775/50	6505	504	63	2232	283			3 × 150	
239*	200QJ10-791/51	6625	514	63	2232	283			3 × 150	
240*	200QJ10-806/52	6745	524	63	2232	283			3 × 150	
241*	200QJ10-822/53	6865	534	63	2232	283			3 × 150	
242*	200QJ10-837/54	6985	544	63	2232	283			3 × 150	
243*	200QJ10-853/55	7105	554	63	2232	283			3 × 185	
244*	200QJ10-868/56	7225	564	63	2232	283			3 × 185	
245*	200QJ10-884/57	7345	574	75	2332	304			3 × 185	
246*	200QJ10-899/58	7465	584	75	2332	304			3 × 240	
247*	200QJ10-915/59	7585	594	75	2332	304			3 × 240	
248*	200QJ10-930/60	7705	604	75	2332	304			3 × 240	
249*	200QJ10-946/61	7945	614	75	2332	304			3 × 240	
250*	200QJ10-961/62	8065	624	75	2332	304			3 × 240	
251*	200QJ10-977/63	8185	634	75	2332	304			3 × 240	
252*	200QJ10-992/64	8305	644	75	2332	304			3 × 240	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diamete
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
253*	200QJ10-1008/65	8425	654	75	2332	304			3 × 240	
254*	200QJ10-1023/66	8545	664	75	2332	304			3 × 240	
255	200QJ20-40/3	436	42	4	670	67			3 × 2.5	
256	200QJ20-54/4	554	48	5.5	690	70			3 × 2.5	
257	200QJ20-67/5	672	55	7.5	705	72			3 × 4	
258	200QJ20-81/6	908	63	7.5	705	72			3 × 4	
259	200QJ20-93/7	1026	72	9.2	750	79			3 × 6	
260	200QJ20-108/8	1144	81	11	765	85			3 × 6	
261	200QJ20-121/9	1262	90	13	780	87		2	3 × 6	
262	200QJ20-133/10	1380	99	15	815	90			3 × 6	
263	200QJ20-148/11	1498	108	15	815	90			3 × 6	
264	200QJ20-160/12	1616	117	18.5	870	107			3 × 10	
265	200QJ20-175/13	1734	126	18.5	870	107			3 × 10	
266	200QJ20-186/14	1852	135	18.5	870	107			3 × 10	
267	200QJ20-202/15	1970	144	22	1030	124.5			3 × 16	
268	200QJ20-212/16	2088	153	22	1030	1030			3 × 16	184
269	200QJ20-226/17	2206	162	25	1100	131.5			3 × 25	
270	200QJ20-243/18	2324	171	25	1100	131.5	2850		3 × 25	
271	200QJ20-252/19	2442	180	25	1100	131.5			3 × 25	
272	200QJ20-270/20	2560	189	30	1165	145.5			3 × 25	
273	200QJ20-283/21	2678	198	30	1165	145.5			3 × 25	
274	200QJ20-297/22	2914	207	30	1165	145.5			3 × 35	
275	200QJ20-305/23	3032	216	30	1165	145.5			3 × 35	
276	200QJ20-320/24	3150	225	37	1245	163			3 × 35	
277	200QJ20-338/25	3268	234	37	1245	163			3 × 50	
278	200QJ20-350/26	3386	243	37	1245	163			3 × 50	
279	200QJ20-363/27	3504	252	37	1245	163		2.5	3 × 50	
280	200QJ20-372/28	3622	261	37	1245	163			3 × 50	
281*	200QJ20-385/29	3740	270	45	1725	202			3 × 50	
282*	200QJ20-400/30	3858	279	45	1725	202			3 × 70	
283*	200QJ20-413/31	3976	288	45	1725	202			3 × 70	
284*	200QJ20-425/32	4094	297	45	1725	202			3 × 70	
285*	200QJ20-437/33	4212	306	45	1725	202			3 × 70	
286*	200QJ20-450/34	1330	315	45	1725	202			3 × 70	
287*	200QJ20-465/35	4448	324	55	1885	217			3 × 95	
288*	200QJ20-478/36	4566	333	55	1885	217			3 × 95	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
289*	200QJ20-490/37	4684	342	55	1885	217			3 × 95	
290*	200QJ20-505/38	4945	351	55	1885	217			3 × 95	
291*	200QJ20-519/39	5062	360	55	1885	217			3 × 95	
292*	200QJ20-532/40	5185	369	63	2232	283			3 × 95	
293*	200QJ20-545/41	5305	378	63	2232	283			3 × 120	
294*	200QJ20-558/42	5545	387	63	2232	283			3 × 120	
295*	200QJ20-572/43	5665	396	63	2232	283			3 × 120	
296*	200QJ20-585/44	5785	405	63	2232	283			3 × 120	
297*	200QJ20-598/45	5905	414	63	2232	283			3 × 120	
298*	200QJ20-612/46	6025	423	75	2332	304			3 × 150	
299*	200QJ20-625/47	6145	432	75	2332	304			3 × 150	
300*	200QJ20-638/48	6265	441	75	2332	304		2.5	3 × 150	
301*	200QJ20-652/49	6385	450	75	2332	304			3 × 150	
302*	200QJ20-665/50	6505	459	75	2332	304			3 × 150	
303*	200QJ20-678/51	6625	468	75	2332	304			3 × 150	
304*	200QJ20-692/52	6745	477	75	2332	304			3 × 150	184
305*	200QJ20-705/53	6865	486	90	2422	323			3 × 185	
306*	200QJ20-718/54	6985	495	90	2422	323	2850		3 × 185	
307*	200QJ20-732/55	7105	504	90	2422	323			3 × 185	
308*	200QJ20-745/56	7225	513	90	2422	323			3 × 240	
309*	200QJ20-758/57	7345	522	90	2422	323			3 × 240	
310*	200QJ20-771/58	7465	531	90	2422	323			3 × 240	
311*	200QJ20-785/59	7585	540	90	2422	323			3 × 240	
312*	200QJ20-798/60	7825	549	90	2422	323			3 × 240	
313*	200QJ20-811/61	7945	568	90	2422	323			3 × 240	
314*	200QJ20-825/62	8065	577	90	2422	323			3 × 240	
315*	200QJ20-838/63	8185	586	90	2422	323			3 × 240	
316*	200QJ20-851/64	8305	595	100	2492	338			3 × 240	
317*	200QJ20-865/65	8425	604	100	2492	338			3 × 240	
318*	200QJ20-878/66	8545	613	100	2492	338		3	3 × 240	
319*	200QJ20-891/67	8665	622	100	2492	338			3 × 240	
320*	200QJ20-904/68	8785	631	100	2492	338			3 × 240	
321*	200QJ20-918/69	8905	640	100	2492	338			3 × 240	
322*	200QJ20-931/70	9025	649	100	2492	338			3 × 240	
323*	200QJ20-944/71	9145	658	110	2542	349			3 × 300	
324*	200QJ20-958/72	9265	667	110	2542	349			3 × 300	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
325*	200QJ20-971/73	9385	676	110	2542	349	2850	3	3 × 300	184
326*	200QJ20-984/74	9505	685	110	2542	349			3 × 300	
327*	200QJ20-998/75	9625	694	110	2542	349			3 × 400	
328	200QJ32-26/2	350	24	4	670	67		2.5	3 × 2.5	
329	200QJ32-39/3	485	33	5.5	690	70			3 × 4	
330	200QJ32-52/4	620	42	7.5	705	72			3 × 4	
331	200QJ32-65/5	755	51	11	765	85			3 × 6	
332	200QJ32-78/6	1008	60	11	765	85			3 × 6	
333	200QJ32-91/7	1143	76	13	780	87			3 × 6	
334	200QJ32-104/8	1278	82	15	815	90			3 × 6	
335	200QJ32-117/9	1413	91	18.5	870	107			3 × 10	
336	200QJ32-130/10	1548	104	18.5	870	107			3 × 10	
337	200QJ32-143/11	1683	113	22	1030	124.5			3 × 10	
338	200QJ32-156/12	1818	122	25	1100	131.5			3 × 16	
339	200QJ32-169/13	1953	131	25	1100	131.5			3 × 16	
340	200QJ32-182/14	2088	140	30	1165	145.5			3 × 16	
341	200QJ32-195/15	2223	149	30	1165	145.5			3 × 25	
342	200QJ32-208/16	2358	158	37	1245	163			3 × 25	
343	200QJ32-221/17	2493	167	37	1245	163			3 × 25	
344	200QJ32-234/18	2628	175	37	1245	163			3 × 25	
345	200QJ32-247/19	2898	184	37	1245	163			3 × 35	
346*	200QJ32-260/20	3033	193	45	1725	202			3 × 35	
347*	200QJ32-273/21	3168	202	45	2542	349			3 × 35	
348*	200QJ32-286/22	3303	211	45	2542	349			3 × 50	
349*	200QJ32-299/23	3438	220	55	1885	217			3 × 50	
350*	200QJ32-312/24	3573	229	55	1885	217			3 × 50	
351*	200QJ32-325/25	3708	238	55	1885	217			3 × 70	
352*	200QJ32-338/26	3843	247	55	1885	217			3 × 70	
353*	200QJ32-351/27	4040	256	63	2232	283		3	3 × 70	
354*	200QJ32-364/28	4175	265	63	2232	283			3 × 70	
355*	200QJ32-377/29	4310	274	63	2232	283			3 × 70	
356*	200QJ32-390/30	4445	283	63	2232	283			3 × 70	
357*	200QJ32-403/31	4580	292	63	2232	283			3 × 95	
358*	200QJ32-416/32	4715	301	75	2332	304			3 × 95	
359*	200QJ32-429/33	4850	310	75	2332	304			3 × 95	
360*	200QJ32-442/34	4985	319	75	2332	304			3 × 95	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
361*	200QJ32-455/35	5120	328	75	2332	304	2850	3	3 × 95	184
362*	200QJ32-468/36	5390	337	75	2332	304			3 × 120	
363*	200QJ32-481/37	5525	346	90	2422	323			3 × 120	
364*	200QJ32-494/38	5660	355	90	2422	323			3 × 150	
365*	200QJ32-507/39	5795	364	90	2422	323			3 × 150	
366*	200QJ32-520/40	5930	373	90	2422	323			3 × 150	
367*	200QJ32-533/41	6065	382	90	2422	323			3 × 150	
368*	200QJ32-546/42	6200	391	90	2422	323			3 × 150	
369*	200QJ32-559/43	6335	400	90	2422	323			3 × 150	
370*	200QJ32-572/44	6470	409	100	2492	338			3 × 150	
371*	200QJ32-585/45	6605	418	100	2492	338			3 × 150	
372*	200QJ32-598/46	6740	427	100	2492	338			3 × 150	
373*	200QJ32-611/47	6875	436	100	2492	338			3 × 185	
374*	200QJ32-624/48	7010	445	110	2492	338			3 × 240	
375*	200QJ32-637/49	7145	454	110	2492	338			3 × 240	
376*	200QJ32-650/50	7280	463	110	2492	338			3 × 240	
377	200QJ40-26/2	350	20	5.5	690	70		2.5	3 × 4	
378	200QJ40-39/3	485	30	7.5	705	72			3 × 4	
379	200QJ40-52/4	620	40	9.2	750	79			3 × 6	
380	200QJ40-65/5	755	50	13	780	87			3 × 6	
381	200QJ40-78/6	1008	67	15	815	90			3 × 6	
382	200QJ40-91/7	1143	77	18.5	870	107			3 × 6	
383	200QJ40-104/8	1278	87	22	1030	124.5			3 × 10	
384	200QJ40-117/9	1413	97	22	1030	124.5			3 × 10	
385	200QJ40-130/10	1548	107	25	1100	131.5			3 × 10	
386	200QJ40-143/11	1683	117	25	1100	131.5			3 × 10	
387	200QJ40-156/12	1818	127	30	1165	145.5			3 × 16	
388	200QJ40-169/13	1953	137	30	1165	145.5			3 × 16	
389	200QJ40-182/14	2088	147	37	1245	163			3 × 25	
390	200QJ40-195/15	2223	157	37	1245	163			3 × 25	
391	200QJ40-208/16	2358	167	37	1245	163			3 × 35	
392*	200QJ40-221/17	2493	177	45	1725	202		3	3 × 35	
393*	200QJ40-234/18	2628	187	45	1725	202			3 × 35	
394*	200QJ40-247/19	2898	197	45	1725	202			3 × 50	
395*	200QJ40-260/20	3033	207	55	1885	217			3 × 50	
396*	200QJ40-273/21	3168	217	55	1885	217			3 × 50	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
397*	200QJ40-286/22	3303	227	63	2232	283	2850	3	3 × 70	184
398*	200QJ40-299/23	3438	237	63	2232	283			3 × 70	
399*	200QJ40-312/24	3573	247	63	2232	283			3 × 70	
400*	200QJ40-325/25	3708	257	75	2332	304			3 × 70	
401*	200QJ40-338/26	3843	267	75	2332	304			3 × 95	
402*	200QJ40-351/27	4040	277	75	2332	304			3 × 95	
403*	200QJ40-364/28	4175	287	75	2332	304			3 × 95	
404*	200QJ40-377/29	4310	297	90	2422	323			3 × 95	
405*	200QJ40-390/30	4445	307	90	2422	323			3 × 120	
406*	200QJ40-403/31	4580	317	90	2422	323			3 × 120	
407*	200QJ40-416/32	4715	327	90	2422	323			3 × 120	
408*	200QJ40-429/33	4850	337	90	2422	323			3 × 120	
409*	200QJ40-442/34	4985	347	90	2422	323			3 × 120	
410*	200QJ40-455/35	5120	357	100	2492	338			3 × 150	
411*	200QJ40-468/36	5390	367	100	2492	338			3 × 150	
412*	200QJ40-481/37	5525	377	100	2492	338			3 × 150	
413*	200QJ40-494/38	5660	387	110	2542	349			3 × 185	
414*	200QJ40-507/39	5795	397	110	2542	349			3 × 185	
415*	200QJ40-520/40	5930	407	110	2542	349			3 × 185	
416*	200QJ40-533/41	6065	417	110	2542	349			3 × 185	
417	200QJ50-13/1	220	14	4	670	67			3 × 2.5	
418	200QJ50-26/2	365	25	5.5	690	70			3 × 4	
419	200QJ50-39/3	510	36	9.2	750	79			3 × 4	
420	200QJ50-52/4	655	44	11	765	85			3 × 6	
421	200QJ50-65/5	800	55	15	815	90			3 × 6	
422	200QJ50-78/6	1080	69	18.5	870	107			3 × 6	
423	200QJ50-91/7	1225	81	22	1030	124.5			3 × 10	
424	200QJ50-104/8	1370	92	25	1100	131.5			3 × 10	
425	200QJ50-117/9	1515	103	30	1165	145.5			3 × 16	
426	200QJ50-130/10	1660	114	30	1165	145.5			3 × 16	
427	200QJ50-143/11	1805	125	30	1165	145.5			3 × 16	
428	200QJ50-156/12	1950	136	37	1245	163			3 × 25	
429	200QJ50-169/13	2095	147	37	1245	163			3 × 25	
430	200QJ50-182/14	2240	158	45	1350	182			3 × 25	
431	200QJ50-195/15	2385	169	45	1350	182			3 × 25	
432*	200QJ50-208/16	2530	180	55	1885	217			3 × 35	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
433*	200QJ50-221/17	2675	191	55	1885	217	2850	3	3 × 50	184
434*	200QJ50-234/18	2965	202	55	1885	217			3 × 50	
435*	200QJ50-247/19	3280	213	63	2232	283		4	3 × 50	
436*	200QJ50-260/20	3430	224	63	2232	283			3 × 50	
437*	200QJ50-273/21	3580	235	63	2232	283			3 × 50	
438*	200QJ50-286/22	3730	246	75	2332	304			3 × 70	
439*	200QJ50-299/23	3880	257	75	2332	304			3 × 70	
440*	200QJ50-312/24	4030	268	75	2332	304			3 × 70	
441*	200QJ50-325/25	4180	279	75	2332	304			3 × 70	
442*	200QJ50-338/26	4330	290	90	2422	323			3 × 95	
443*	200QJ50-351/27	4480	301	90	2422	323			3 × 95	
444*	200QJ50-364/28	4630	312	90	2422	323			3 × 95	
445*	200QJ50-377/29	4780	323	90	2422	323			3 × 95	
446*	200QJ50-390/30	4930	334	100	2492	338			3 × 120	
447*	200QJ50-403/31	5080	345	100	2492	338			3 × 120	
448*	200QJ50-416/32	5230	356	100	2492	338			3 × 120	
449*	200QJ50-429/33	5380	367	100	2492	338			3 × 120	
450*	200QJ50-442/34	5530	378	100	2492	338			3 × 120	
451*	200QJ50-455/35	5680	389	110	2542	349			3 × 150	
452*	200QJ50-468/36	5830	400	110	2542	349			3 × 150	
453*	200QJ50-481/37	5980	411	110	2542	349			3 × 185	
454	200QJ63-12/1	220	12	4	670	67		3	3 × 2.5	
455	200QJ63-24/2	365	22	7.5	705	72			3 × 4	
456	200QJ63-36/3	510	31	11	765	85			3 × 6	
457	200QJ63-48/4	655	42	15	815	90			3 × 6	
458	200QJ63-60/5	800	54	18.5	870	107			3 × 6	
459	200QJ63-72/6	1080	76	22	1030	124.5			3 × 10	
460	200QJ63-84/7	1225	94	25	1100	131.5			3 × 10	
461	200QJ63-96/8	1370	116	30	1165	145.5			3 × 16	
462	200QJ63-105/5	1028	138	30	1165	145.5			3 × 16	
463	200QJ63-126/6	1173	160	37	1245	163			3 × 16	
464	200QJ63-147/7	1318	182	45	1350	172			3 × 25	
465	200QJ63-168/8	1463	204	55	1510	197			3 × 35	
466	200QJ63-189/9	1690	226	55	1510	197			3 × 35	
467*	200QJ63-210/10	1840	248	63	2232	283		4	3 × 50	
468*	200QJ63-231/11	1990	270	75	2332	304			3 × 50	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
469*	200QJ63-252/12	2140	292	75	2332	304			3 × 70	
470*	200QJ63-273/13	2290	314	90	2422	323			3 × 70	
471*	200QJ63-294/14	2440	336	90	2422	323			3 × 95	
472*	200QJ63-315/15	2590	358	90	2422	323			3 × 95	
473*	200QJ63-336/16	2740	380	100	2492	338			3 × 120	
474*	200QJ63-357/17	2890	402	110	2542	349			3 × 120	
475	200QJ80-18/1	298	35	7.5	705	72			3 × 4	
476	200QJ80-36/2	443	45	13	780	87			3 × 6	
477	200QJ80-54/3	588	55	18.5	870	107			3 × 10	
478	200QJ80-72/4	883	69	25	1100	131.5			3 × 10	
479	200QJ80-90/5	1028	91	30	1165	145.5			3 × 16	
480	200QJ80-108/6	1173	113	37	1245	163			3 × 16	
481	200QJ80-126/7	1318	135	45	1350	182			3 × 25	
482	200QJ80-144/8	1463	157	55	1510	197			3 × 25	
483*	200QJ80-162/9	1690	179	63	2232	283			3 × 35	184
484*	200QJ80-180/10	1840	201	75	2332	304		4	3 × 50	
485*	200QJ80-198/11	1990	223	75	2332	304			3 × 50	
486*	200QJ80-216/12	2140	245	90	2422	323	2850		3 × 70	
487*	200QJ80-234/13	2290	267	90	2422	323			3 × 70	
488*	200QJ80-252/14	2440	289	100	2492	338			3 × 70	
489*	200QJ80-270/15	2590	311	100	2492	338			3 × 70	
490*	200QJ80-288/16	2740	333	110	2542	349			3 × 95	
491	200QJ80-11/1	308	32	4	670	67			3 × 2.5	
492	200QJ80-22/2	463	42	7.5	705	72			3 × 4	
493	200QJ80-33/3	618	52	11	765	85			3 × 6	
494	200QJ80-44/4	773	62	15	815	90			3 × 6	
495	200QJ80-55/5	928	72	18.5	870	107			3 × 10	
496	200QJ80-66/6	1083	82	22	1030	124.5			3 × 10	
497	200QJ80-77/7	1396	93	30	1165	145.5			3 × 16	
498	200QJ80-88/8	1551	114	30	1165	145.5			3 × 16	
499	200QJ80-99/9	1706	135	37	1245	163			3 × 16	
500	200QJ80-110/10	1861	156	37	1245	163			3 × 16	
501	200QJ80-121/11	2016	177	45	1350	182			3 × 16	
502	250QJ32-138/6	1125	110	22	981	143.6			3 × 10	
503	250QJ32-161/7	1260	125	25	1001	149.6	2875	2.5	3 × 16	233
504	250QJ32-184/8	1395	140	30	1036	160.6			3 × 16	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 高度 Height	配套潜水电机 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
505	250QJ32-207/9	1530	155	37	1076	165.6	2875	2.5	3 × 25	233
506	250QJ32-230/10	1665	170	37	1076	165.6			3 × 25	
507	250QJ32-253/11	1800	185	45	1141	170.6			3 × 35	
508	250QJ32-276/12	1935	200	45	1141	170.6			3 × 50	
509*	250QJ32-300/13	2070	215	55	1644	200.6		3	3 × 50	
510*	250QJ32-322/14	2205	230	55	1644	200.6			3 × 50	
511*	250QJ32-345/15	2340	245	63	1889	241			3 × 70	
512*	250QJ32-368/16	2475	260	63	1889	241			3 × 70	
513*	250QJ32-391/17	2610	275	63	1889	241			3 × 95	
514*	250QJ32-414/18	2880	290	75	2039	296			3 × 95	
515*	250QJ32-437/19	3015	305	75	2039	296			3 × 95	
516*	250QJ32-460/20	3150	320	75	2039	296			3 × 120	
517*	250QJ32-483/21	3285	335	90	2159	310			3 × 120	
518*	250QJ32-506/22	3420	350	90	2159	310			3 × 150	
519*	250QJ32-529/23	3555	365	110	2349	345			3 × 185	
520*	250QJ32-552/24	3690	380	110	2349	345			3 × 185	
521*	250QJ32-575/25	3825	395	110	2349	345			3 × 185	
522*	250QJ32-598/26	3960	410	110	2349	345			3 × 185	
523*	250QJ32-621/27	4095	425	110	2349	345			3 × 240	
524*	250QJ32-644/28	4230	440	110	2349	345			3 × 240	
525*	250QJ32-667/29	4395	455	125	2561	597			3 × 240	
526*	250QJ32-690/30	4500	470	125	2561	597			3 × 240	
527*	250QJ32-713/31	4635	485	125	2561	597			3 × 240	
528*	250QJ32-736/32	4770	500	140	2731	602			3 × 300	
529*	250QJ32-759/33	4905	515	140	2731	602			3 × 300	
530*	250QJ32-782/34	5040	530	140	2731	602			3 × 300	
531*	250QJ32-805/35	5310	545	140	2731	602			3 × 400	
532*	250QJ32-828/36	5445	560	160	2821	612			3 × 400	
533*	250QJ32-851/37	5580	575	160	2821	612			3 × 400	
534*	250QJ32-874/38	5714	590	160	2821	612			3 × 400	
535*	250QJ32-897/39	5850	605	160	2821	612			3 × 400	
536*	250QJ32-920/40	5985	620	160	2821	612			3 × 400	
537	250QJ40-126/6	1125	117	25	1001	150.6			3 × 10	
538	250QJ40-147/7	1260	135	30	1036	160.6			3 × 16	
539	250QJ40-168/8	1395	153	37	1076	165.6			3 × 25	
540	250QJ40-189/9	1530	171	37	1076	165.6			3 × 25	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
541	250QJ40-210/10	1665	189	45	1141	170.6	2875	3	3 × 35	233
542	250QJ40-231/11	1800	207	45	1141	170.6			3 × 35	
543	250QJ40-252/12	1935	225	55	1216	180.6			3 × 50	
544	250QJ40-273/13	2070	243	55	1216	180.6			3 × 50	
545*	250QJ40-294/14	2205	261	63	1889	241			3 × 70	
546*	250QJ40-315/15	2340	279	63	1889	241			3 × 70	
547*	250QJ40-336/16	2475	297	75	2039	296			3 × 95	
548*	250QJ40-357/17	2610	315	75	2039	296			3 × 95	
549*	250QJ40-378/18	2880	333	75	2039	296			3 × 95	
550*	250QJ40-399/19	3015	351	90	2159	310			3 × 120	
551*	250QJ40-420/20	3150	369	90	2159	310			3 × 120	
552*	250QJ40-441/21	3285	387	90	2159	310			3 × 120	
553*	250QJ40-462/22	3420	405	110	2349	345			3 × 150	
554*	250QJ40-483/23	3555	423	110	2349	345			3 × 185	
555*	250QJ40-504/24	3690	441	110	2349	345			3 × 185	
556*	250QJ40-525/25	3825	459	125	2561	597			3 × 185	
557*	250QJ40-546/26	3960	477	125	2561	597			3 × 240	
558*	250QJ40-567/27	4095	495	125	2561	597			3 × 240	
559*	250QJ40-588/28	4230	513	140	2731	602			3 × 240	
560*	250QJ40-609/29	4395	531	140	2731	602			3 × 240	
561*	250QJ40-630/30	4500	549	140	2731	602			3 × 300	
562*	250QJ40-651/31	4635	567	140	2731	602			3 × 300	
563*	250QJ40-672/32	4770	585	160	2821	612			3 × 300	
564*	250QJ40-693/33	4905	603	160	2821	612			3 × 400	
565*	250QJ40-714/34	5040	621	160	2821	612			3 × 400	
566*	250QJ40-735/35	5310	639	160	2821	612			3 × 400	
567	250QJ50-20/1	316	33	5.5	690	70			3 × 4	
568	250QJ50-40/2	476	48	9.2	750	79			3 × 4	
569	250QJ50-60/3	636	63	13	780	87			3 × 6	
570	250QJ50-80/4	994	88	18.5	961	135.6			3 × 6	
571	250QJ50-100/5	1154	104	22	981	143.6			3 × 10	
572	250QJ50-120/6	1314	119	25	1001	150.6			3 × 16	
573	250QJ50-140/7	1474	135	30	1036	160.6			3 × 16	
574	250QJ50-160/8	1634	150	37	1076	165.6			3 × 25	
575	250QJ50-180/9	1794	166	45	1141	170.6			3 × 25	
576	250QJ50-200/10	1954	181	45	1141	170.6			3 × 25	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
577	250QJ50-220/11	2114	197	55	1216	180.6	2875	3	3 × 35	233
578	250QJ50-240/12	2274	212	55	1216	180.6			3 × 50	
579	250QJ50-260/13	2434	228	63	1461	231			3 × 50	
580	250QJ50-280/14	2594	243	63	1461	231			3 × 50	
581	250QJ50-300/15	2754	258	63	1461	231			3 × 70	
582*	250QJ50-320/16	3074	273	75	2039	396			3 × 70	
583*	250QJ50-340/17	3234	288	90	2159	310			3 × 95	
584*	250QJ50-360/18	3394	303	90	2159	310			3 × 95	
585*	250QJ50-380/19	3554	318	110	2349	396			3 × 120	
586*	250QJ50-400/20	3714	333	110	2349	396			3 × 120	
587*	250QJ50-420/21	3874	348	110	2349	396		4	3 × 150	
588*	250QJ50-440/22	4034	363	110	2349	396			3 × 150	
589*	250QJ50-460/23	4194	378	110	2349	396			3 × 150	
590*	250QJ50-480/24	4354	393	125	2561	597			3 × 185	
591*	250QJ50-500/25	4514	408	125	2561	597			3 × 185	
592*	250QJ50-520/26	4674	423	125	2561	597			3 × 185	
593*	250QJ50-540/27	4834	438	140	2731	602			3 × 240	
594*	250QJ50-560/28	5154	453	140	2731	602			3 × 240	
595*	250QJ50-580/29	5314	468	140	2731	602			3 × 240	
596*	250QJ50-600/30	5474	483	160	2821	612			3 × 300	
597*	250QJ50-620/31	5634	498	160	2821	612			3 × 300	
598*	250QJ50-640/32	5794	513	160	2821	612			3 × 300	
599*	250QJ50-660/33	5954	528	160	2821	612			3 × 400	
600*	250QJ50-680/34	6114	543	160	2821	612			3 × 400	
601	250QJ80-20/1	285	22.2	7.5	705	72			3 × 4	
602	250QJ80-40/2	420	38.6	15	815	90			3 × 6	
603	250QJ80-60/3	555	55	22	981	143.6			3 × 10	
604	250QJ80-80/4	860	88.6	30	1036	160.6			3 × 16	
605	250QJ80-100/5	995	105	37	1076	165.6			3 × 16	
606	250QJ80-120/6	1130	121.4	45	1141	170.6			3 × 16	
607	250QJ80-140/7	1265	137.8	55	1216	180.6			3 × 25	
608	250QJ80-160/8	1400	154.2	55	1216	180.6			3 × 25	
609	250QJ80-180/9	1535	170.6	63	1461	231			3 × 35	
610	250QJ80-200/10	1670	187	75	1611	274			3 × 50	
611*	250QJ80-220/11	1805	203.4	90	2159	310			3 × 70	
612*	250QJ80-240/12	1940	219.8	90	2159	310			3 × 70	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
613*	250QJ80-260/13	2075	236.2	90	2159	310	2875	4	3 × 70	233
614*	250QJ80-280/14	2210	252.6	110	2349	345			3 × 95	
615*	250QJ80-297/11	3060	269	110	2349	345			3 × 95	
616*	250QJ80-324/12	3280	285.4	125	2561	597			3 × 120	
617*	250QJ80-351/13	3500	301.8	125	2561	597			3 × 150	
618*	250QJ80-378/14	3720	318.2	140	2731	602			3 × 150	
619*	250QJ80-405/15	3940	334.6	160	2821	312			3 × 185	
620*	250QJ80-432/16	4160	351	160	2821	312			3 × 240	
621*	250QJ80-459/17	4380	367.4	185	2931	626			3 × 240	
622*	250QJ80-486/18	4600	383.8	185	2931	626			3 × 240	
623*	250QJ80-513/19	4820	400.2	220	3091	660			3 × 300	
624*	250QJ80-540/20	5040	416.6	220	3091	660			3 × 300	
625*	250QJ80-567/21	5260	433	220	3091	660			3 × 300	
626*	250QJ80-594/22	5480	449.4	220	3091	660			3 × 300	
627	250QJ100-18/1	285	20	7.5	705	72			3 × 4	
628	250QJ100-36/2	420	35	15	815	90			3 × 6	
629	250QJ100-54/3	555	50	25	1001	150.6			3 × 16	
630	250QJ100-72/4	860	65	30	1036	160.6			3 × 16	
631	250QJ100-90/5	995	98	45	1141	170.6			3 × 25	
632	250QJ100-108/6	1130	117	45	1141	170.6			3 × 25	
633	250QJ100-126/7	1365	136	55	1216	180.6			3 × 25	
634	250QJ100-144/8	1400	155	63	1461	231			3 × 35	
635	250QJ100-162/9	1535	174	75	1611	274			3 × 35	
636*	250QJ100-180/10	1670	193	90	2159	310			3 × 50	
637*	250QJ100-198/11	1805	212	90	2159	310			3 × 50	
638*	250QJ100-216/12	1940	231	110	2349	345			3 × 70	
639*	250QJ100-225/9	2400	250	110	2349	345		5	3 × 70	
640*	250QJ100-250/10	2620	269	110	2349	345			3 × 95	
641*	250QJ100-275/11	3060	288	125	2561	597			3 × 95	
642*	250QJ100-300/12	3280	307	140	2731	602			3 × 120	
643*	250QJ100-325/13	3500	326	160	2821	612			3 × 150	
644*	250QJ100-350/14	3720	345	160	2821	612			3 × 185	
645*	250QJ100-375/15	3940	364	185	2931	626			3 × 240	
646*	250QJ100-400/16	4160	383	185	2931	626			3 × 240	
647*	250QJ100-425/17	4380	402	220	3091	660			3 × 240	
648*	250QJ100-450/18	4600	421	220	3091	660			3 × 240	

序号 No.	型号 Type	潜水泵 Submersible Pump		配套潜水电机 Matching Submersible Motor			转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		高度 Height	重量 Weight	功率 Power	高度 Height	重量 Weight				
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
649*	250QJ100-475/19	4820	440	220	3091	660	2875	5	3 × 240	233
650	250QJ125-16/1	315	29.4	9.2	750	79			3 × 4	
651	250QJ125-32/2	480	44.4	18.5	961	135.6			3 × 6	
652	250QJ125-48/3	645	59.4	25	1001	150.6			3 × 16	
653	250QJ125-64/4	810	74.4	37	1076	165.6			3 × 16	
654	250QJ125-80/5	1145	109	45	1141	170.6			3 × 16	
655	250QJ125-96/6	1310	124	55	1216	180.6			3 × 25	
656	250QJ125-112/7	1475	139	63	1461	231			3 × 35	
657	250QJ125-128/8	1640	154	75	1611	274			3 × 35	
658	250QJ125-144/9	1805	169	90	1731	299			3 × 50	
659	250QJ125-160/10	1970	184	90	1731	299			3 × 50	
660	250QJ125-176/11	2135	199	110	1921	324			3 × 70	
661*	250QJ125-202/9	2400	214	110	2349	345			3 × 70	
662*	250QJ125-225/10	2620	229	125	2561	597			3 × 95	
663*	250QJ125-247/11	3060	244	140	2731	602			3 × 95	
664*	250QJ125-270/12	3280	259	160	2821	612			3 × 120	
665*	250QJ125-292/13	3500	274	160	2821	612			3 × 150	
666*	250QJ125-315/14	3720	289	185	2931	626			3 × 185	
667*	250QJ125-338/15	3940	304	185	2931	626			3 × 185	
668*	250QJ125-360/16	4160	319	220	3091	660			3 × 240	
669*	250QJ125-383/17	4380	334	220	3091	660			3 × 240	
670	250QJ140-15/1	315	28	9.2	815	79			3 × 6	
671	250QJ140-30/2	480	48	18.5	961	135.6			3 × 6	
672	250QJ140-45/3	645	68	30	1036	160.6			3 × 16	
673	250QJ140-60/4	810	88	37	1076	165.6			3 × 16	
674	250QJ140-75/5	1145	108	45	1141	170.6			3 × 16	
675	250QJ140-90/6	1310	128	55	1216	180.6			3 × 25	
676	250QJ140-105/7	1475	148	63	1461	231			3 × 35	
677	250QJ140-120/8	1640	168	75	1161	274			3 × 35	
678	250QJ140-135/9	1805	188	90	1731	299			3 × 50	
679	250QJ140-150/10	1970	208	90	1731	299			3 × 50	
680*	250QJ140-165/11	2135	228	110	2349	345			3 × 50	
681*	250QJ140-180/12	2300	248	110	2349	345			3 × 70	
682*	250QJ140-189/9	2400	268	110	2349	345			3 × 70	
683*	250QJ140-210/10	2620	288	125	2561	597			3 × 95	
684*	250QJ140-231/11	3060	308	140	2731	602			3 × 95	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
685*	250QJ140-252/12	3280	328	160	2821	612			3 × 120	
686*	250QJ140-273/13	3500	348	185	2931	626			3 × 150	
687*	250QJ140-294/14	3720	368	185	2931	626			3 × 185	
688*	250QJ140-315/15	3940	388	220	3091	660			3 × 240	
689*	250QJ140-336/16	4160	408	220	3091	660			3 × 240	
690	250QJ150-20/1	420	52	15	815	90			3 × 6	
691	250QJ150-40/2	640	70	30	1036	160.6			3 × 16	
692	250QJ150-60/3	860	88	45	1141	170.6			3 × 25	
693	250QJ150-80/4	1300	144	55	1216	180.6			3 × 25	
694	250QJ150-100/5	1520	162	63	1461	231			3 × 35	
695	250QJ150-120/6	1740	180	75	1611	274			3 × 35	
696	250QJ150-140/7	1960	198	90	1731	299			3 × 50	
697	250QJ150-160/8	2180	216	110	1921	324			3 × 50	
698*	250QJ150-180/9	2400	234	125	2561	597			3 × 70	233
699*	250QJ150-200/10	2620	252	140	2731	602	2875		3 × 95	
700*	250QJ150-220/11	3060	270	160	2821	612		5	3 × 95	
701*	250QJ150-240/12	3280	288	160	2821	612			3 × 120	
702*	250QJ150-260/13	3500	306	185	2931	626			3 × 150	
703*	250QJ150-280/14	3720	324	185	2931	626			3 × 150	
704*	250QJ150-300/15	3940	342	220	3091	660			3 × 185	
705	250QJ160-15/1	420	50	11	765	85			3 × 6	
706	250QJ160-30/2	640	70	22	981	143.6			3 × 16	
707	250QJ160-45/3	860	120	37	1076	165.6			3 × 25	
708	250QJ160-60/4	1080	140	45	1141	170.6			3 × 25	
709	250QJ160-75/5	1520	160	55	1216	180.6			3 × 25	
710	250QJ160-18/1	420	180	13	780	87			3 × 6	
711	250QJ160-36/2	640	200	25	1001	150.6			3 × 16	
712	250QJ160-54/3	860	220	37	1076	165.6			3 × 16	
713	250QJ160-72/4	1300	240	55	1216	180.6			3 × 25	
714	250QJ160-90/5	1520	260	63	1461	231			3 × 35	
715	300QJ140-21/1	420	49	13	780	87			3 × 6	
716	300QJ140-42/2	640	72	25	1001	150.6			3 × 16	
717	300QJ140-63/3	860	118	37	1076	165.6	2900		3 × 16	281
718	300QJ140-84/4	1300	140	55	1216	180.6			3 × 25	
719	300QJ140-105/5	1520	162	63	1619	462			3 × 35	
720	300QJ140-126/6	1740	184	75	1659	481			3 × 35	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 高度 Height	配套潜水电机 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
721	300QJ140-147/7	1960	206	90	1714	507			3 × 50	
722	300QJ140-168/8	2180	228	110	1784	540			3 × 70	
723	300QJ140-189/9	2400	250	110	1784	540			3 × 70	
724*	300QJ140-210/10	2620	272	125	2398	702		5	3 × 95	
725*	300QJ140-231/11	3060	294	140	2518	722			3 × 95	
726*	300QJ140-252/12	3280	316	160	2668	747			3 × 120	
727*	300QJ140-273/13	3500	338	185	2768	788			3 × 150	
728*	300QJ140-294/14	3720	360	185	2768	788			3 × 185	
729*	300QJ140-315/15	3940	382	220	2938	821		6	3 × 240	
730*	300QJ140-336/16	4160	404	220	2938	821			3 × 240	
731*	300QJ140-357/17	4380	426	220	2938	821			3 × 240	
732	300QJ160-25/1	400	50	18.5	961	135.6			3 × 16	
733	300QJ160-50/2	600	100	37	1076	165.6			3 × 16	
734	300QJ160-30/1	400	50	22	981	143.6			3 × 16	
735	300QJ160-60/2	600	100	45	1141	170.6			3 × 25	
736	300QJ160-90/3	1050	160	63	1619	462			3 × 35	
737	300QJ200-15/1	400	50	13	780	87			3 × 6	281
738	300QJ200-20/1	400	50	18.5	961	135.6	2900		3 × 6	
739	300QJ200-30/2	600	70	25	1001	150.6		5	3 × 16	
740	300QJ200-40/2	600	70	37	1076	165.6			3 × 16	
741	300QJ200-60/3	800	100	55	1216	180.6			3 × 25	
742	300QJ200-80/4	1250	158	75	1659	481			3 × 35	
743	300QJ200-100/5	1450	188	90	1714	507			3 × 50	
744	300QJ200-120/6	1650	218	110	1784	540			3 × 50	
745	300QJ200-140/7	1850	248	125	1874	602			3 × 70	
746	300QJ200-160/8	2050	278	140	1994	622			3 × 95	
747	300QJ200-180/9	2250	308	160	2144	647			3 × 95	
748*	300QJ200-200/10	2450	338	185	2768	788			3 × 120	
749*	300QJ200-220/11	2650	368	220	2938	821			3 × 150	
750*	300QJ200-240/12	3050	398	220	2938	821			3 × 150	
751*	300QJ200-260/13	3250	428	240	3238	821		6	3 × 150	
752*	300QJ200-280/14	3450	458	260	3238	821			3 × 185	
753*	300QJ200-300/15	3650	488	280	3238	821			3 × 240	
754	300QJ210-25/1	400	50	25	1001	150.6			3 × 16	
755	300QJ210-50/2	600	70	45	1141	170.6			3 × 25	
756	300QJ230-20/1	400	71	22	981	143.6			3 × 6	

序号 No.	型号 Type	潜水泵 Submersible Pump 高度 Height	潜水泵 Submersible Pump 重量 Weight	配套潜水电机 Matching Submersible Motor 功率 Power	配套潜水电机 Matching Submersible Motor 高度 Height	配套潜水电机 Matching Submersible Motor 重量 Weight	转速 Rotational speed	出水管直径 Outlet pipe Diameter	配套电缆规格 Matching Cable Specification	电泵最大外径 Pump Maximum External Diameter
		(mm)	(kg)	(kW)	(mm)	(kg)	(rpm)	(")		(mm)
757	300QJ230-40/2	600	75	45	1141	170.6	2900	6	3 × 16	281
758	300QJ230-60/3	800	110	63	1619	462			3 × 25	
759	300QJ230-80/4	1250	140	90	1714	507			3 × 50	
760	300QJ250-15/1	400	75	18.5	961	135.6			3 × 6	
761	300QJ250-30/2	600	100	37	1076	165.6			3 × 16	
762	300QJ250-24/1	430	75	30	1036	160.6			3 × 16	
763	300QJ250-48/2	660	135	55	1216	180.6			3 × 25	
764	300QJ250-72/3	1140	185	90	1714	507			3 × 50	
765	300QJ320-28/1	430	77	45	1141	170.6		8	3 × 16	
766	300QJ320-56/2	660	160	75	1659	481			3 × 35	
767	300QJ320-84/3	1140	260	110	1784	540			3 × 50	
768	350QJ250-25/1	573	73	30	1036	160.6		6	3 × 25	330
769	350QJ250-50/2	851	125	63	1619	462			3 × 35	
770	350QJ250-75/3	1389	180	90	1714	507			3 × 50	
771	350QJ250-100/4	1667	235	125	1874	640			3 × 70	
772	350QJ250-125/5	1945	290	160	2144	602			3 × 95	
773	350QJ320-30/1	573	74	45	1036	170.6		8	3 × 25	
774	350QJ320-60/2	851	151	90	1714	507			3 × 50	
775	350QJ320-90/3	1389	228	140	1994	622			3 × 70	
776	350QJ320-120/4	1667	305	160	2144	647			3 × 95	
777	350QJ320-20/1	573	74	30	1036	160.6			3 × 16	
778	350QJ320-40/2	851	151	63	1619	462			3 × 35	
779	400QJ400-50/1	640	100	90	1714	507			3 × 50	377
780	400QJ500-20/1	640	100	45	1141	170.6			3 × 16	
781	400QJ500-40/1	640	100	90	1714	507			3 × 50	
782	400QJ500-80/2	1230	200	185	2244	688			3 × 120	

备注：表中加 * 号的型号要求配有可调多极止推轴向力承载装置。

Remark: The model marked with an asterisk (*) in the table shall be provided with an adjustable multipolar thrust axial force bearing device as required.

性能曲线图 Performance curves



150QJ5-7.14/1



150QJ10-7.14/1



150QJ20-6.5/1



150QJ25-8/1
150QJ32-6/1



150QJ40-8/1
150QJ50-6/1



175QJ10-15/1
175QJ15-14/1
175QJ20-13/1



175QJ32-12/1



175QJ40-12/1



175QJ50-12/1



200QJ10-15.5/1



200QJ20-13.3/1



200QJ32-13/1



200QJ40-13/1



200QJ50-13/1



200QJ63-12/1



200QJ80-11/1



200QJ63-21/1



250QJ32-23/1



250QJ50-20/1



250QJ80-20/1
250QJ100-18/1



250QJ125-18/1
250QJ140-16/1



250QJ150-20/1
250QJ160-18/1
300QJ140-21/1



300QJ200-20/1
300QJ160-25/1



300QJ320-28/1



350QJ320-30/1



400QJ500-40/1

数据更新，恕不另行通知。
Data is subject to changes without notice beforehand.

安装示意图 Installation diagram



型号选择单 Type Selection Form

工作条件 Working conditions

水井最佳涌水量
maximum water outflow of well _____ (m^3/h)

设计要求流量
designed discharge capacity _____ (m^3/h)

水井静水位
well static water level _____ (m)

设计要求流量时动水位
dynamic water level at designed discharge capacity _____ (m)

泵座出口处最低表压力
minimum gage pressure at outlet of pump base _____ (Mpa)

水井成井的总深度
total depth of finished well _____ (m)

泵预计安装深度
estimated installing depth of pump _____ (m)

水井成井至预计安装深度的最小井径
minimum well diameter from finished well to estimated installing depth _____ (mm)

水井成井至预计安装深度井筒是否正直
straight or not of well shaft from finished well to estimated installing depth _____

(将直径等于电泵的最大外径，长度为 6m 的圆柱体用扬水管下放到泵预计的安装深度而不受阻，则认为井是直的)
(Whether the well is straight or not can be tested by the following method: If a cylinder, with its diameter equal to the maximum external diameter of electric pump and with a length of 6 meters, can be slid down to the estimated mounting depth of pump with pumping tube smoothly, the well can be regarded as straight.)

水源类型(细砂层、卵石层、裂隙层、江水、河水)
The type of water source (fine sand layer, pebble layer, crevice layer, river water) _____

其它方面
Others _____

使用条件 Use conditions

井水最高温度
Maximum temperature of well water _____ (℃)

水中固体物质(重量百分比)含量
Content of solid matter (weight percentage) in the water _____ (%)

水的酸碱(PH)值
Value of PH in the water _____

水中固体物质最大和最小粒度
Max. & min. grain size of solid matter in the water _____ (mm)

水中是否有油类
Is there any oil contented in the water _____

供电系统变压器容量
Transformer capacity of the power supplying system _____ (KVA)

变压器至水井距离
Distance from transformer to well _____ (m)

变压器至水井输电材质 / 线径
Material and diameter of transmission wire from transformer to well _____ (mm)

电源通常电压范围
Normal voltage range of power source _____ (V) 至 to _____ (V)

其它方面
Others _____

选择潜水电泵型号及成套供货要求
Selection of submersible electric pump type and requirements for packaged delivery of set unit

选择潜水泵型号 / 台数
Type and units of submersible pump _____

选择潜水电机型号 / 台数
Type and units of submersible motor _____

成套供货要求
Package delivery _____

用户单位(签字 / 盖章)
Client (signature/stamp) _____